



Concealed Automatic Door Operator

An automatic door looks best when you can't see how it works — the operator concealed above the false ceiling, no header box, the ceiling line running clean through the opening. But an automatic door is a machine that needs maintenance, and when the operator is buried behind a fixed ceiling, every service visit starts with opening the ceiling.

MF Services specifies, supplies and installs Portalp RS automatic doors with the RS header inspection hatch — a made-to-length hatch that conceals the mechanism within the false ceiling and doubles as the service access.

Key Stats

6 m
custom lengths up to six metres, made to the opening

100 mm
low-profile header — 100mm high, 230mm deep

3
detection and security radars integrate into the hatch

¼ turn
cam locks open the hatch for quick, secure access

Engineered for the Ceiling Line

The RS header inspection hatch fixes directly to the door's end caps and conceals the mechanism within the false ceiling. Quarter-turn cam locks open it for maintenance, holding bars keep it open, and detection radars integrate into the hatch itself — delivered as a single unit with the operator, RAL-finished to sit with the ceiling.

Why Architects Specify It

Concealed, Not Buried

An automatic pedestrian door isn't fit-and-forget: EN 16005 assumes it's kept in a safe condition through its working life, which means regular inspection and planned maintenance. A door that can't be reached can't be maintained — and a maintenance regime that starts with dismantling the ceiling is one that quietly stops happening.



A Ceiling That Stays Clean

Sleek, minimalist and RAL-finished to the ceiling, with radars integrated into the hatch rather than surface-mounted. The opening reads the way you drew it.



Serviceable By Design

Quarter-turn cam locks, holding bars and secure anti-lift fixings make every maintenance visit quick, safe and repeatable — no lifted tiles, no cut plasterboard.



One Unit, One Install

The hatch arrives as a single unit with the RS door operator — specified, installed and maintained by MF Services as one assembly.

Specifier Questions

Which doors does it work with?

Portalp RS sliding and two-leaf telescopic automatic doors, single or double — delivered as a single unit with the operator, so it's specified with the door rather than added after.

How long can the hatch be?

Custom lengths up to six metres, matched to the opening — with hangers added on longer hatches to keep the assembly rigid and stable.

Can MF Services help specify it?

Yes — from early design through to installation and aftercare.

Let's talk.

Contact us for technical specification support, or to talk through your project.

contact@mfservices.ie | +353 21 434 8996 | mfservices.ie